

US 20030137780A1

## (19) United States

## (12) Patent Application Publication (10) Pub. No.: US 2003/0137780 A1 Fontana, JR. et al. (43) Pub. Date: Jul. 24, 2003

- (54) HIGH LINEAR DENSITY TUNNEL JUNCTION FLUX GUIDE READ HEAD WITH IN-STACK LONGITUDINAL BIAS STACK (LBS)
- (75) Inventors: Robert Edward Fontana JR., San
  Jose, CA (US); Kuok San Ho,
  Cupertino, CA (US); Tao Pan, San
  Jose, CA (US); Ching Hwa Tsang,
  Sunnyvale, CA (US)

Correspondence Address:
Ron Feece
INTERNATIONAL BUSINESS MACHINES
CORPORATION
Dept. L2PA
5600 Cottle Road
San Jose, CA 95193 (US)

(73) Assignee: INTERNATIONAL BUSINESS MACHINES CORPORATION

(21) Appl. No.: 10/054,352

(22) Filed: Jan. 18, 2002

## **Publication Classification**

(57) ABSTRACT

Several embodiments of a sense current perpendicular to the planes of the sensor (CPP) and flux guide type of read head has a gap between first and second shield layers at an air bearing surface (ABS) where the flux guide is located which is less than a gap between the first and second shield layers at a recessed location where the sensor is located. This reduced gap increases the linear bit density capability of the read head. A longitudinal bias stack (LBS) is located in the sensor stack. Several unique methods of construction are described for forming the magnetic head assemblies.

